



xTHERM 60U

room thermostat

The room thermostat is an integral part of the evoFLOOR X controller. It is installed in a selected room, such as the living room, and is designed to maintain the preset temperature there. The thermostat's OLED display provides information about the room temperature, operating mode, and schedules. BT wireless communication enables control of the thermostat via the ecoNET Cloud mobile application.

ecoNET Cloud Android




ecoNET Cloud iOS



Plum Sp. z o.o.
ul. Wspólna 19, Ignatki, 16-001 Kleosin, Poland
National Waste Database No. 000009381

hvac.plum.pl
hvac@plum.pl

ISSUE
1.0b, 19.09.2025



technical data

supply / power consumption	230 VAC, 50 Hz / 1.7 W
protection degree	IP 20
relative humidity	5..85%
operating temperature	0...40 °C
storage temperature	-25...60 °C
temperature measurement range/ accuracy	internal: 0...40 °C / ±1,0 °C external: 0...40 °C / ±2,0 °C
temperature hysteresis	0.2...5 °C
display	OLED 1.29', 128x64 pix. with backlight
control	2 x touch buttons – capacitive
communication	BT v4.2 LE with the ecoNET Cloud application
screw terminals	wire cross-section: 0.5...2.5 mm²
dimensions	80x80x35 mm
installation	standard installation box Ø 60 mm

